



## **CURRAN INTERNATIONAL ANNOUNCES NEW “FLEX-LANCE” TECHNIQUE SAVING TIME AND COST; IMPROVING POWER PLANT OPERATIONS**

*Adaptation of patented tube ID coating technique accelerates in-situ condenser tube lining applications for corrosion protection*

**Houston (October 11, 2007)** – Curran International, Inc., a leading coatings application provider serving the global power, petrochemicals, HVAC and shipping industries, announced it has developed a newer, faster and more flexible method for applying polymer-based protective coatings to tubing in huge condenser water boxes operating in power plants. The new technique deploys a “flex-lance” apparatus that extends as much as 60 feet down the tubing within a small water box.

The technique, incorporating thin film applications technology patented by Curran International, facilitates full length tube coating from “inside the box” without disassembling waterboxes or headers. This solution offers clients in-situ cleaning and coating of corroded condenser tube IDs at a fraction the cost or schedule requirement of retubing.

“Our innovative technique for cleaning the interior walls of small-diameter tubes in condenser water boxes gives plant managers one less headache to deal with,” said Ed Curran, chief executive officer of Curran International. “The flex-lance application technique can then coat even the most obscure spots inside the tubing in the heat-transfer equipment, preparing the surface walls with a grit-blasting technique as well.”

The new flex-lance system uses patented applications technology for applying coating to full circumferential wall of tubes typically 1.00” of less in outer diameter. The flex-lance system can be passed through a 18” manway at the waterbox or header; once set up a technician can coat full length tubes to 60’ in length. A thin film (<.003”) of polymer lining is atomized and driven onto the inner surface of the full length tube as the lance travels down the tube. The application has been used to recover corroded condenser tubes at several power plants. In a unique application a steam ship condenser with failing tubes was repaired with coating in less than 10 days.

Tube cleaning to “white metal” is a surface-preparation standard required before applying protective thin-film coatings. The coatings application improves resistance to corrosion, fouling and other common tubing blockages. This treatment also drastically reduces plant shutdowns and equipment stoppages for required maintenance and cleanings, positively impacting operational efficiency, asset utilization and equipment performance. The use of thin-film linings has saved energy, petrochemical and power generation clients millions of dollars annually in extra energy consumption and maintenance costs by improving the performance of fixed equipment running cooling water. The application of thin-film tube ID linings has been used for more than 50 years for cooling-water heat exchangers operating at refineries, power generation and petrochemical plants.

###

Curran International is an applicator of protective linings with a full service coating facility near Houston. Curran International has provided global field maintenance services to power generation, refining and industrial clients since 1982. Curran developed and patented a method to apply thin-film polymer linings to



full-length tube IDs more than 10 years ago. In that time, it has coated thousands of heat exchanger bundles in service at petroleum and chemical processing operations. [www.curranintl.com](http://www.curranintl.com).

Media Contact:  
Suzy Ginsburg  
Tel: 713.721-4774  
[suzy@gcomworks.com](mailto:suzy@gcomworks.com)